

## MAX<sup>APS</sup> series

Maximum output generators  
that take your fog to  
the MAX.

- Extremely powerful, adjustable fog output
- Virtually noiseless, with the finest fog and the longest hanging times
- Automatic Purging System (APS) to prevent build-up and clogging
- Compatible with remote control timer and DMX interface
- Detachable remote control and 8 m (26 ft) cable included

MAX 3000<sup>APS</sup>



- Powerful fog output (up to 85 m<sup>3</sup>/3,000 ft<sup>3</sup> per minute)
- Portability option

MAX 5000<sup>APS</sup>



- More powerful fog output (up to 218 m<sup>3</sup>/7,680 ft<sup>3</sup> per minute)
- Portability option

MAX 5000<sup>APS</sup> H·O·



- Maximum fog output (up to 445 m<sup>3</sup>/15,750 ft<sup>3</sup> per minute)
- Operates with N<sub>2</sub> only



### TECHNICAL DATA

	MAX 3000 <sup>APS</sup>	MAX 5000 <sup>APS</sup>	MAX 5000 <sup>APS</sup> H-O-
Maximum fog output per minute	85 m <sup>3</sup> (3,000 ft <sup>3</sup> )	218 m <sup>3</sup> (7,680 ft <sup>3</sup> )	445 m <sup>3</sup> (15,750 ft <sup>3</sup> )
Fluid consumption per hour	1 L (34 oz) at 2.76 bar (40 psi)	2.6 L (88 oz) at 2.76 bar (40 psi)	4.5 L (1.2 US gallon) at 4.14 bar (60 psi)
Gas type	CO <sub>2</sub> or N <sub>2</sub>	CO <sub>2</sub> or N <sub>2</sub>	N <sub>2</sub> only
Gas consumption per hour	0.97 kg (2.13 lb) at 2.76 bar (40 psi)	2.25 kg (5 lb) at 2.76 bar (40 psi)	5 kg (11 lb) at 4.14 bar (60 psi)
Reservoir capacity	2.5 L (0.66 US gallon)	2.5 L (0.66 US gallon)	6.5 L (1.7 US gallon)
Automatic Purging System (APS)	Standard feature	Standard feature	Standard feature
Fog colour	Pure white	Pure white	Pure white
Particle size	0.5-0.7 microns	0.5-0.7 microns	0.5-0.7 microns
Warm-up time (maximum)	8 minutes	8 minutes	8 minutes
Fluid type (M.S.D.S. available on request)	MDG Neutral Fluid	MDG Neutral Fluid	MDG Neutral Fluid
Operating voltage	115 or 230 VAC, 50/60 Hz	115 or 230 VAC, 50/60 Hz	208 VAC 1Ø or 230 VAC, 50/60 Hz
Power consumption	715 W	1,415 W	2,815 W
Dimensions	<b>Length</b> 61 cm (24") <b>Width</b> 18 cm (7") <b>Height</b> 30 cm (12")	<b>Length</b> 61 cm (24") <b>Width</b> 28 cm (11") <b>Height</b> 30 cm (12")	<b>Length</b> 68.5 cm (27") <b>Width</b> 28 cm (11") <b>Height</b> 30 cm (12")
Weight	20 kg (43 lb)	26 kg (56 lb)	33 kg (72 lb)
Shipping weight (with flight case)	33 kg (72 lb)	38 kg (85 lb)	44 kg (97 lb)
Approval	CE approved, CSA and UL pending	CE approved, CSA and UL pending	CE approved, CSA and UL pending

### OPTIONS AND ACCESSORIES

**Portability option**  
(3000<sup>APS</sup> and 5000<sup>APS</sup> only)  
CO<sub>2</sub> adapter secures gas canister horizontally below machine.



**Remote control timer**  
Program your fog emission in advance.



**Interfaces**  
DMX interface and translator.



**Flight case**  
Durable for safe and easy transport.



### FLUID

**MDG Neutral Fluid**  
Safe, non-toxic, with the longest hanging time. Available in 4 L (1 US gallon), 20 L (5.3 US gallon) and 205 L (55 US gallon) sizes.



The manufacturer has the right, without notice, to modify and improve products as deemed necessary.

**DISTRIBUTED BY:**

